MARINE

Your Safety, Our Technology

DCD-CE3M

Marine Approved Conventional Combined Rate of Rise & Fixed Temperature Heat Detector (90°C)

Features

- Electronic linear heat detection
- Remote indicator output
- Wide voltage range (9.5 ~ 30 V dc)
- Twin fire LEDs allow 360° viewing
- Approved by LPCB and GL



Description

Model DCD-CE3M is a Marine Approved Rate of Rise Heat Detector with a 90°C fixed temperature element using a thermistor and linearising circuit to provide an accurate linear response Heat Detector.

The DCD-CE3M is ideal for use where medium ambient temperatures exist, such as drying rooms or where Smoke Detectors are unsuitable because of the presence of steam or cooking fumes such as in a kitchen/galley.

The DCD-CE3M is supported on the majority of conventional systems. A third terminal provides remote indicator output.

Specification

Ordering Code	DCD-CE3M
Operating Voltage	9.5 – 30 V dc
Quiescent Current (typ)	35 °A
Maximum Current in Alarm (typ)	40 mA
Remote Indicator Drive	20 mA (max) / 9.5-14 mA (typ)
Operating Temperature Range	-10 °C to +50 °C
Storage Temperature Range	-30 °C to +70 °C
Maximum Humidity	95% RH - Non Condensing (at 40 °C)
Ingress Protection Rating	IP63
Colour / Case Material	Ivory or White / Polycarbonate
Weight (g) / Diameter (mm) / Height (mm)	76 / 100 / 38
Compatible Base	YBN-R/6M
Base Fixing Centres (mm)	48 ~ 74
Approvals to (EN54:2000) Class A1 & A1R	LPCB & GL

Ordering Codes

Product	Part Number
Instrinsically Safe Conventional Rate of Rise Heat Detector	DCD-CE3M
Instrinsically Safe Conventional Rate of Rise Heat Detector (White)	DCD-CE3M(WHT)

Approvals

LPCB 0007 · DNV·GL MARITIME

HOCHIKI

ISS2JAN19

For further information visit www.hochikieurope.com/marine

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.