Public Address and Audio / Amplifiers

DSPPA-MP250UB

DSPPA



Features

- Mini digital mixer
- 250W
- Amplifier
- USB/FM/Bluetooth player
- General public address system
- Supports MP3
- Remote control
- 1.5U

Specifications

Brand	DSPPA
Model	MP250UB
Range	Installation
Output power	1 x 250 W
Zones or channels	1 channel with 1 volume control zone
Speaker outputs	Line 70 V / 100 V Low impedance (4-16 ?)
Built-in player	Player MP3 from USB Bluetooth Receiver FM radio receiver
Remote control	Infrared remote control included
Microphone inputs	MIC1: Front Jack 6,35 mm (priority) MIC2: XLR + Jack Combo 6,35 mm, Selectable Phantom Power 48V MIC3/TO2: Selectable split, XLR + Jack combo 6,35 mm, selectable phantom power 48V Input sensitivity: 10 mV ±1 mV MIC frequency response: 120 Hz ~ 12 kHz (±3 dB)
Auxiliary inputs	AUX1: RCA AUX2: RCA shared with MIC3 Input sensitivity: 350 mV ±50 mV AUX Frequency Response: 80 Hz ~ 15 kHz (±3 dB)
Control inputs	1 EMC input via Euroblock terminal with maximum priority for emergency audio 1 relay input for MUTE 1 relay input for SIREN trigger
Entry priority	MUTE > EMC = Alarm = Chime > MIC1 > Other
Audio outputs	IN/OUT: RCA
Controls	Master volume Independent volume control per input Tone control: Bass, Treble Select USB/FM/Bluetooth source Warning tone trigger button
Indicators	Segmented LCD status display Signal LED Power LED
Compatible Accessories	Not determined
Frequency response	MIC: 120 Hz ~ 12 kHz (±3 dB) AUX: 80 Hz ~ 15 kHz (±3 dB)
Power supply	Built-in power supply; AC 110-120 V or 200-240 V, 50/60 Hz
ENVIRONMENT	Operating temperature: -10 °C ~ +50 °C Relative humidity: 20 % ~ 80 %

Type of mounting	Desktop Tray in rack
Dimensions	363 × 292 × 106 mm
Weight	3 kg