SensoIRIS MIO04 IP65

Addressable Output Module



- IP 65 Protection
- Transparent lid
- Easy mounting

SensoIRIS MIO04 IP65 is an programmable output module, designed for application in addressable fire alarm systems, supporting TTE communication protocol. The module is mounted in a separate plastic box suitable for wall mounting with IP65 protection and possible for outdoor installations. The module controls 4 relay outputs, which could be programmed and get activated by different events in the system. SensoIRIS MIO04 IP65 is powered by the fire alarm panel and can be controlled via the communication protocol.

Features

- IP 65 Protection
- 4 programmable relay outputs
- Build-in isolator
- Enclosure box
- PC material
- Transparent lid for module status reading
- More room for cables inside the box

Technical Specifications

Operating Voltage Range	16 - 32VDC
Consumption, stand-by mode	175µA@27VDC
Nom. current consumption	200µA@27VDC
Outputs, electrical characteristics (max.)	DC 30V/1A; AC 125V/0.5A
Current consumption with 1 LED on	4mA
Wire Gauge for terminals	0.4mm2 - 2.0mm2
Operating temperature	-10°C to +60°C
Relative humidity resistance	(93 ± 3)% @ 40°C

Last update: 07.2024

info@teletek-electronics.bg
teletek-electronics.com